



Ever lasting



Non-Absorbing



Recycled



Weather Proof

Plaswood Product Range - SQUARE BASED BOLLARDS

Plaswood bollards are uniquely manufactured from 100% recycled waste agricultural polythene films. This waste film is mostly used silage wrap and is recovered from farms throughout the UK and Ireland. It is this feedstock which gives Plaswood bollards the exceptional high strength properties which are far superior to its competitors.

The environmental credentials for all Plaswood products are without parallel. The collected waste agricultural films are recycled into plastic pellets and re-manufactured into Plaswood at BPI Recycled Products ES 14001 accredited factory in Dumfries. This is the only factory in the UK capable of recycling these waste materials. Plaswood does not rot, splinter, discolour or degrade with age. It is maintenance free, is resistant to most chemicals and can itself be fully recycled at the end of its working life.

Chamfered Square with Bands

Order Codes:
 Black RS017300 | Brown RS017301

BLACK OR BROWN

Chamfered Square

Order Code: RS017306

**Square Black 120
 Grass / Verge Protection**

Order Code: RS07284

**Square Black 100
 Grass / Verge Protection**

Order Code: RS07283

**Square Black 150
 Grass / Verge Protection**

Order Code: RS07285

Plaswood Range

- ✓ Signage
- ✓ Planters
- ✓ Litter Bins
- ✓ Picnic Tables
- ✓ Lumber & Fencing
- ✓ Bollards & Gates

✓ **Tough** ✓ **Durable** ✓ **Strong** ✓ **Wide Range**

✓ **Versatile** ✓ **Environmentally Friendly** ✓ **Low Maintenance**

Unless otherwise stated, Plaswood Bollards require a minimum below ground depth of 450mm to 500mm and 400mm square. Setting in concrete to a strength of 23kN is preferred. Positioning pegs are available for keying into the concrete where bollards are supplied with a pre-drilled hole located approximately 200mm up from the base. All bollards are black unless stated otherwise.



Ever lasting



Non-Absorbing



Recycled



Weather Proof

Plaswood Product Range - ROUND BASED BOLLARDS

Plaswood round based bollards are available in a range of diameters. A choice of round or square tops are available, together with options for banding. All round based bollards are black and 1500mm in length.

SIZES AVAILABLE

Product	Diameter	Pallet Quantity	Weight (per bollard)
RS017283	100mm	70	9.65kg
RS017284	120mm	60	14.58kg
RS017285	150mm	50	23.56kg

CHOOSE FROM TOP STYLES:

- Chamfer top
- Dome top
- Flat top

CLASS 1 DIAMOND GRADE BANDING AVAILABLE:

- 20mm in red, white or half red/ half white
- 50mm in red, white or half red/ half white
- 80mm in red, white or half red/ half white

When ordering please specify style of top required and if banding is required please specify size, colour and quantity. Standard banding is 1 x 50mm, 1 x 80mm or 3 x 20mm. If you have other requirements please discuss with our sales team.



Plaswood Range

- ✓ Signage
- ✓ Planters
- ✓ Litter Bins
- ✓ Picnic Tables
- ✓ Lumber & Fencing
- ✓ Bollards & Gates

- ✓ Tough
- ✓ Durable
- ✓ Strong
- ✓ Wide Range
- ✓ Versatile
- ✓ Environmentally Friendly
- ✓ Low Maintenance

Unless otherwise stated, Plaswood Bollards require a minimum below ground depth of 450mm to 500mm and 400mm square. Setting in concrete to a strength of 23kN is preferred. Positioning pegs are available for keying into the concrete where bollards are supplied with a pre-drilled hole located approximately 200mm up from the base. All bollards are black unless stated otherwise.



Ever lasting



Non-Absorbing



Recycled



Weather Proof

Plaswood Product Range - BOLLARD EXTRAS

Steel Inserts to improve high impact resistance	
RS017299	1
	2 - 10
	11 - 20
	21+
Red and / or white reflective plates	
Approximate size - 70mm x 110mm	
Sockets - Removable / Lockable	
RS017313	To suit 120mm diameter bollard
RS017314	To suit 150mm diameter bollard
RS017315	To suit 150mm square bollard
Sockets - Surface Mounted	
RS017318	To suit 120mm diameter bollard
RS017316	To suit 150mm diameter bollard
RS017317	To suit 150mm square bollard
Sockets - Knock-Down Bollard	
RS017320	To suit 120mm diameter bollard
RS017319	To suit 150mm diameter bollard
RS017321	To suit 150mm square bollard
Black - with a choice of white or red reflective panel	
Size 30mm x 90mm x 1000mm	
RS01794	Delineator with white panel
RS01795	Delineator with red panel



Delineators



Surface Mounted Socket



Plaswood Range

- ✓ Signage
- ✓ Planters
- ✓ Litter Bins
- ✓ Picnic Tables
- ✓ Lumber & Fencing
- ✓ Bollards & Gates

✓ Tough ✓ Durable ✓ Strong ✓ Wide Range

✓ Versatile ✓ Environmentally Friendly ✓ Low Maintenance

Unless otherwise stated, Plaswood Bollards require a minimum below ground depth of 450mm to 500mm and 400mm square. Setting in concrete to a strength of 23kN is preferred. Positioning pegs are available for keying into the concrete where bollards are supplied with a pre-drilled hole located approximately 200mm up from the base. All bollards are black unless stated otherwise.